

Sheds, garages and garage door warranties

Warranties are available upon application for:

COLORBOND® steel and ZINCALUME® steel material used in the manufacture of Shed/Garage roofing and walling in Australian applications.

- Sheds and Garages must be erected on a concrete slab footing.
- Must have fully enclosed (i.e. 4-walls) floor area $\geq 18\text{m}^2$.
- Walling material must have base-metal thickness (BMT) $\geq 0.35\text{mm}$.
- Roofing material must have BMT $\geq 0.42\text{mm}$.

COLORBOND® steel material used in the manufacture of Garage Doors in Australian applications.

These warranties:

- Do not extend to the roof battens or frame.
- Are the same for Residential and Commercial applications.

All warranties are subject to exclusions, application and eligibility criteria*.

Distance from marine influence	Sheds and Garages (roof/wall)		Garage Doors
	COLORBOND® steel	ZINCALUME® steel	COLORBOND® steel
>5km	20yrs Corrosion to perforation, and flake and peel	18yrs Corrosion to perforation	10yrs Corrosion to perforation
1-5km	15yrs Corrosion to perforation, and flake and peel	15yrs Corrosion to perforation	10yrs Corrosion to perforation
<1km	No warranty		

Please note that these warranty periods are indicative and could vary depending on specific circumstances of installation.

Builders and distributors can create additional benefit for their customers by applying for a pre-approved warranty

